

Photoelectric Sensor Lineup



from
\$60.75

5 mm, C5 series

- Power: 10-30 VDC
- Embedded cable or M8 Q/D
- 3-wire, NPN/PNP output
- Fixed sensitivity



from
\$80.00
pair

8 mm, HE series thru-beam

- Power: 10-30 VDC
- Embedded cable or M8 Q/D
- 3-wire, NPN or PNP output,
- Fixed sensitivity



from
\$34.00

12 mm, DM series

- Power: 10-30 VDC
- Embedded cable or M12 Q/D
- 4-wire, NPN/PNP output, LO/DO selectable
- Teach auto calibration



from
\$34.00

18 mm non-metal, SS/MS/MV series

- Power: 10-30 VDC or 20-250VAC
- Embedded cable or M12 Q/D
- 4-wire, NPN/PNP output, triac output
- Fixed sensitivity



from
\$33.00

18 mm metal, C18 series

- Power: 10-36 VDC
- Embedded cable or M12 Q/D
- 3-wire, NPN/PNP output
- Adjustable sensitivity
- Axial or right-angle optics



from
\$40.25

18 mm non-metal, FA series

- Power: 10-30 VDC
- Embedded cable or M12 Q/D
- 4 wire, NPN/PNP output
- Laser or LED, fixed sensitivity



from
\$91.75

AC/DC rectangular, FG series

- Universal voltage, 12-240 VDC, 24-240 VAC
- Embedded cable
- 3A SPDT relay output
- Adjustable sensitivity



from
\$61.75

Mini DC Rectangular, FE Series

- Power: 10-30 VDC
- Embedded cable or M8 Q/D
- 3-wire, NPN/PNP output, LO/DO selectable switch
- Adjustable sensitivity



from
\$39.25

DC rectangular, CX series

- Embedded cable or M8 Q/D
- 3-wire, NPN/PNP output
- Adjustable sensitivity



from
\$52.50

DC rectangular, QX series

- Power: 10.8-30 VDC
- Embedded cable or M12 Q/D
- 4-wire, NPN/PNP output,
- Adjustable sensitivity



from
\$67.00

DIN rail fiber amplifiers, DFT and DFP series

- Power: 10-30 VDC
- Embedded cable or M8 Q/D
- 3-wire, NPN/PNP output, LO/DO selectable via user interface



from
\$44.00

Cutler-Hammer Enhanced 50 Series

- Drop-in replacement for A-B 9000 series
- Diffuse, polarized reflex, through-beam and clear object detection



from
\$41.25

18 mm fiber amplifier, SSF series

- Power: 10-30 VDC
- Embedded cable or M12 Q/D
- 4-wire, NPN/PNP output, LO/DO selectable
- Teach auto calibration



from
\$24.75

Cutttable fibers, CF series

- 2.2 mm Ø Diameter
- Length 2 m, field cuttable
- Use with DFP/DFT/SSF series



from
\$360.50
pair

Light screens, BX series

- Power: 12-24 VDC
- M12 Q/D
- 4-wire, NPN/PNP output, NO/NC selectable
- Screen measures 2 m x 70 mm
- 12 light beams, 5 mm resolution

Photoelectric Sensors Selection Guide



Specification	FA Series LED DC	FA Series Laser DC	SS Series DC	MS Series DC
Description	18mm plastic, DC	18mm plastic, DC	18mm plastic, DC	18mm plastic with background suppression, DC
Sensing Distances	Diffuse models: 1m Reflective models: 3m Through-beam: 20m	Diffuse models: 300mm Reflective models: 20m Through-beam: 50m	Diffuse models: 100mm, 200mm, 400mm Reflective models: 2m Through-beam models: 8m	Diffuse Reflection Standard distance models: 50mm Extended distance models: 100mm
Output State	Complementary N.O / N.C.	Complementary N.O / N.C.	N.O. / N.C. selectable	N.O. / N.C. selectable
Logic Output	NPN / PNP	NPN / PNP	NPN / PNP	NPN / PNP selectable
Connection Type	Axial cable / M12 connector	Axial cable / M12 connector	Axial cable / M12 connector	Axial cable / M12 connector
Supply Voltage	10-30VDC	10-30VDC	10-30VDC	10-30VDC
Switching Frequency	250Hz	Diffuse and reflective models: 800Hz Through-beam models: 1kHz	Diffuse and reflective models: 250Hz Through-beam models: 25Hz	80Hz
Rating	IEC IP67	IEC IP67	IEC IP67	IEC IP67
Page	18-8	18-11	18-14	18-17



Specification	FARS Series DC	MQ Series AC	MV Series AC	C5 Series DC	HE/HER Series DC
Description	18 mm diffuse with background suppression	18 mm diffuse with background suppression, 90° radial optic	18mm plastic, AC	5mm stainless steel, DC	8 mm Thru-Beam
Sensing Distances	30 to 130 mm	Standard distance models: 50mm Extended distance models: 100mm	Diffuse: 100mm, 200mm, 400mm Reflective: 3m Through-beam: 16m	Diffuse models: 50mm Through-beam models: 250mm	1000 mm / Ex. gain = 2
Output State	N.O./N.C. background suppression Light-on/Dark-on selectable Q/Qnot	N.O. / N.C. background suppression	N.O./ receiver dependent	N.O. / receiver dependent	N.O. / N.C.
Logic Output	NPN/PNP	Triac	Triac	NPN / PNP / N.O. only	NPN / PNP
Connection Type	Axial cable M12 quick disconnect	M12 quick disconnect	Axial cable M12 connector	Axial cable M8 connector	Axial cable M8 quick disconnect
Supply Voltage	10-30VDC	20-253VAC	20-253VAC	10-30VDC	10-30VDC
Switching Frequency	1 kHz	25Hz	25Hz	250Hz	10kHz
Rating	IEC IP67	IEC IP67	IEC IP67	IEC IP67	IEC IP67
Page	18-19	18-22	18-24	18-27	18-29

- PLC Overview
- DL05/06 PLC
- DL105 PLC
- DL205 PLC
- DL305 PLC
- DL405 PLC
- Field I/O
- Software
- C-more HMIs
- Other HMI
- AC Drives
- Motors
- Steppers/Servos
- Motor Controls
- Proximity Sensors
- Photo Sensors**
- Limit Switches
- Encoders
- Current Sensors
- Pushbuttons/Lights
- Process
- Relays/Timers
- Comm.
- TB's & Wiring
- Power
- Circuit Protection
- Enclosures
- Appendix
- Part Index

Photoelectric Sensors Selection Guide



Specification	DM Series DC	C18 Series DC	FE Series DC	CX Series DC	QX Series DC
Description	12mm nickel-plated brass with Teach operating distance function, DC	18mm nickel-plated brass, DC	Mini-rectangular plastic, DC	Mini-rectangular plastic, DC	Rectangular plastic, DC
Sensing Distances	Diffuse models: 100mm, 300mm Reflective models: 2m Through-beam: 4m	Diffuse models w/ background suppression: 10 to 120mm Reflective models: 2m	Diffuse models: 800mm Reflective models: 4m Through-beam: 12m	Diffuse models: up to 600mm Diffuse models w/ background suppression: 15 to 150mm Reflective models: Up to 2m Through-beam models: Up to 6m	Diffuse models: 300mm Reflective models: 2.5m Through-beam models: 8m
Output State	Diffuse: N.O./N.C. selectable Polarized reflective: N.O./N.C. selectable Through-beam: N.O./N.C./ receiver dependent	N.O.	Light-on/Dark-on selectable	N.O.	N.O./receiver dependent
Logic Output	NPN / PNP	NPN/PNP/receiver dependent	NPN / PNP	NPN / PNP	NPN/PNP selectable/receiver dependent
Connection Type	Axial cable / M12 connector	Axial cable/M12 connector	Axial cable / M8 connector	Axial cable / M8 connector	Axial cable / M12 connector
Supply Voltage	10-30VDC	10-36VDC	10-30VDC	10-36VDC	10.8-30VDC
Switching Frequency	Diffuse and reflective models: 400Hz Through-beam models: 250Hz	Diffuse models w/ background suppression: 500Hz Reflective models: 1kHz	1kHz	Diffuse models: 1kHz Diffuse models w/ background suppression: 500Hz Reflective models: 1kHz Through-beam models: 1kHz	Diffuse and reflective models: 750Hz (Tr=0.5ms) Through-beam models: 500Hz (Tr=0.75ms)
Rating	IEC IP67	IEC IP67	IEC IP67	IEC IP65	IEC IP65
Page	18-31	18-34	18-37	18-39	18-41



Specification	FG Series AC/DC	CH Enhanced 50 Series
Description	Rectangular plastic, AC/DC	Fiberglass-reinforced plastic
Sensing Distances	Diffuse models: 550mm Reflective models: 9m Through-beam: 20m	Through-beam: 500 ft (152 m) Diffuse models: 10 ft. (3 m) Polarized reflex: 16 ft. (4.9 m) Clear /object detector: 45 in (1.2 m)
Output State	N.O./N.C.	Light-on/Dark-on selectable
Logic Output	SPDT 3A relay	Through-beam: NPN/PNP 250 mA, Solid-state relay 300 mA @ 240 VAC/VDC, SPDT EM relay 3 A @ 120 VAC Diffuse: NPN/PNP 250 mA, Solid-state relay 300 mA @ 240 VAC/VDC, SPDT EM relay 3 A @ 120 VAC Polarized reflex: NPN/PNP 250 mA, Solid-state relay 300 mA @ 240 VAC/VDC, SPDT EM relay 3 A @ 120 VAC Clear object detector: NPN/PNP 250 mA, Solid-state relay 300 mA @ 240 VAC/VDC, SPDT EM relay 3 A @ 120 VAC
Connection Type	Axial cable	Cable or mini/micro connection
Supply Voltage	12-240VDC / 24-240VAC	10 - 40 VDC, 12 - 240 VDC, 24 - 240 VAC
Switching Frequency	33Hz	various
Rating	IEC IP67	IEC IP67
Page	18-44	18-46

Photoelectric Sensors Selection Guide



Specification	DFT Series Fiber Amp	DFP Series Fiber Amp	SSF Series Fiber Amp
Description	Compact rectangular plastic fiber optic amplifier with Teach operating distance function, DC	Compact rectangular plastic fiber optic amplifier, DC	18mm plastic fiber optic amplifier, DC
Sensing Distances	See Optical Fiber Tables following the amplifier's specifications	See Optical Fiber Tables following the amplifier's specifications	See Optical Fiber Tables following the amplifier's specifications
Output State	Light-on / Dark-on selectable	Light-on / Dark-on selectable	Light-on / Dark-on selectable
Logic Output	NPN / PNP	NPN / PNP	NPN / PNP
Connection Type	Axial cable / M8 connector	Axial cable / M8 connector	Axial cable / M12 connector
Supply Voltage	10-30VDC	10-30VDC	10 - 30 VDC
Switching Frequency	1.5kHz	1.5kHz	800Hz
Rating	IEC IP64	IEC IP64	IEC IP67
Page	18-56	18-57	18-58



Specification	CF Series Optical Fibers	BX Series Light Screen
Description	Cutttable diffuse reflection and through-beam fiber optic cables (2.2mm diameter)	Rectangular plastic high resolution area sensor, DC
Sensing Distances	Amplifier dependent. Refer to fiber optic tables for sensing distances.	Through-beam: 2m with 70mm height area
Output State	N/A	Selectable N.O / N.C.
Logic Output	N/A	NPN / PNP
Connection Type	N/A	M12 connector
Supply Voltage	N/A	12 - 24 VDC
Switching Frequency	N/A	-
Rating	IEC IP67	IEC IP67
Page	18-59	18-63

Custom Designed Sensors

AUTOMATIONDIRECT and Microdetectors (MD) have been partners in the sensor business for over 7 years. MD is located in Italy and has been in business for over 30 years. With high quality processes, including UL/CE design procedures, AUTOMATIONDIRECT and MD supply the North American market with industrial quality sensors at a very reasonable price. Based on this engineering quality and engineering design capabilities, MD and AUTOMATIONDIRECT are offering the opportunity for customized products for your special application needs. The MD Custom Design Service can add value to your products by implementing sensing technology ranging from optoelectronics to RFID.

Call 770-844-4200 and ask about custom-designed sensors.



MD has co-designed the following applications:

- Linear optical encoder
- Through-beam sensor for lift applications
- Tobacco sensor
- Moisture sensor for ceramic industry
- Bar code reader for domestic and household appliances field